



# Hydrogen Sulfide Detector-Transmitter E2608-H2S



## Features

- Wall-mount or duct-mount version
- Industrial housing, attached or remote sensor
- Two analog outputs settable to 4-20 mA or 0-10 V
- Two relays for alarm / ventilation control
- RS485 Modbus RTU digital interface

## Specifications

Calibration	Hydrogen Sulfide H <sub>2</sub> S
Sensing method	electrochemical sensor
Sampling method	diffusion
Detection ranges, standard high	0...100 ppm (500 ppm peak) H <sub>2</sub> S 0...1000 ppm (10 000 ppm peak) H <sub>2</sub> S
Resolution	0,1 / 1 ppm H <sub>2</sub> S
Accuracy	< 1 ppm H <sub>2</sub> S
Signal update	every 1 second
Response time	< 30 seconds
Maintenance interval	12 months
Sensor lifetime	> 2 years
Self-diagnostics	full functionality check at start-up
Warm-up time	≤ 1 min
Power supply	11...30 VDC or 90...265 VAC
Power consumption	< 2 W
Digital interface	RS485, Modbus RTU protocol
Analog outputs	2 × 4-20 mA / 0-10 V, user settable
Output relays	2 × SPST relays (closing contact), 250 VAC / 30 VDC, 5 A max
Default alarm set-points	10 ppm / 20 ppm H <sub>2</sub> S
Enclosure	light grey ABS plastic, wall mount, protection class IP65
Dimensions	H85 × W82 × D55 mm
Cable options for remote probe	shielded cable, 2,5 or 5 m
Operating environment	industrial indoor and outdoor locations
Operating conditions	-30...+50 °C, 15...90 %RH

