



Hydrogen Detector-Transmitter E2608-H2



Features

- Industrial housing, attached or remote sensor
- Two relays for alarm / ventilation control
- Two analog outputs settable to 4-20 mA or 0-10 V
- RS485 Modbus RTU digital interface

Specifications

Detected gas	Hydrogen
Calibration	Hydrogen
Sensing method	long-life metal-oxide gas sensor
Sampling method	diffusion
Detection range	0...4 %vol (0...100% LEL)
Resolution / digital unit	100 ppm / 0,01 %vol (0,25% LEL)
Accuracy	± 400 ppm / 0,04 %vol (±1% LEL)
Signal update	every 1 second
Response time	~15 seconds
Maintenance interval	12 months
Sensor lifetime	> 10 years
Self-diagnostics	full functionality check at start-up
Warm-up time	≤ 1 min
Power supply	11...30 VDC or 90...265 VAC
Power consumption	< 2 W
Digital interface	RS485, Modbus RTU protocol
Analog outputs	2 × 4-20 mA / 0-10 V, user settable
Output relays	2 × SPST relays (closing contact), 250 VAC / 30 VDC, 5 A max
Default alarm set-points	1: 0,4 %vol (10%LEL) 2: 1,6 %vol (40%LEL)
Enclosure	light grey ABS plastic, wall mount, protection class IP65
Dimensions	H85 × W82 × D55 mm
Cable options for remote probe	shielded cable, 3, 10 or 25 m
Operating environment	industrial indoor and outdoor locations
Operating conditions	-40...+85 °C, 0...100 %RH

